



Wall Chaser offers the most efficient cutting of clean edged grooves for channels.





- · With dust cover to prevent ingress of dust and dirt
- · Operable with the fingers of the hand holding the top handle





Main top handle with soft grip



Adjustable cutting depth



Electronic control

Overload protection

Adjustable cutting width in 9 stage by

- Soft start
- Constant speed control



Aluminum blade case designed to allow for easy blade replacement



Connectable to vacuum cleaners for clean work environment

Cutting width

Inner flange	

3	Cutting width	Q'ty of 6 mm spacer	Q'ty of 3 mm spacer
	6 mm		1 pc.
	9 mm	1 pc.	
	12 mm	1 pc.	1 pc.
	15 mm	2 pcs.	
	18 mm	2 pcs.	1 pc.
	21 mm	3 pcs.	
	24 mm	3 pcs.	1 pc.
	27 mm	4 pcs.	
	30 mm	4 pcs.	1 pc.

nm	Wall Chaser	SG1251 125mm	(5")	318
	Double Insulation	Continuous rating input Capacity	1,400W Depth : 0-30mm (0 - Width : 6-30mm (1/4	
	Constant Speed	Blade diameter No load speed (rpm)	125mm (5") 10.000	F- 1-3/10 J
	Soft Start	Dimensions (L x W x H)	350x151x178mm (13-3/4"x5-15/16"x7	")
	Dust Collecting	Net weight Power supply cord	4.5kg (9.9lbs) 5.0m (16.4ft)	
	Carrying Case			
		Standard Equipment: Diamond Wheel x2, Hex Wrench, Lock Nut Wrench		

weight according to EPTA-Procedure 01/2003

Items of standar equipment and specifications may vary by country or area



Makita New Zealand Ltd. 15 Orbit Drive, Mairangi Bay PO Box 100 914, North Shore, Fax 0800 600 601 Sales 09 4798251