

SINCE 1896

QUICK RELEASE™ TUBING CUTTERS

FEATURES

- Quick Release[™] is a **Reed invention** and still the industry standard.
- Features include quick release, quick advance and manual advance, along with the ball detent wheel pin.
- Built-in reamer and spare cutter wheel in the knob on TC10, TC1.60 and TC20.
- Simple cutter wheel change permits use on a wide variety of pipe/tubing types.

Quick Release™ Tubing Cutters are the best tracking, easiest cutting tubing cutters available. Cut copper, aluminum, light wall steel and stainless steel tubing. With alternate wheels they will cut a wide variety of plastic pipe and tubing. Reed also offers the R2558 wheel for muffler systems tubing. **TC10**, **TC1.60** and **TC20** sliding bars are die-cast zinc aluminum for great strength. These three sizes also feature a built-in reamer and spare cutter wheel in the knob. Long-proven **TC30** and larger models with steel sliding bars withstand professional workloads over the long haul.

Catalog	Item	O.D. Capacity		Length		Weight		
No.	Code	actual O.D. in	actual O.D. mm	in	mm	lbs	kg	Wheel
TC1Q*	03410	1/8 - 1 ⁵ /16	3 - 33	6	152	0.6	0.3	0
TC1.6Q*	03416	1/4 - 1 5/8	6 - 42	6.5	165	0.8	0.4	0
TC2Q*	03420	1/4 - 2 5/8	6 - 67	8	203	1.2	0.5	0
TC3Q	03430	3/8 - 3 1/2	10 - 90	11	279	2.5	1.1	30-40
TC3Q2558	03439	3/8 - 3 1/2	10 - 90	11	279	2.5	1.1	R2558
TC4Q	03440	1 7/8 - 4 1/2	48 - 114	12	305	2.8	1.3	30-40
TC5Q2558	03459	2 1/2 - 5	63 - 125	13	330	3.0	1.4	R2558
TC6Q	03460	4 - 6 5/8	102 - 168	15	381	3.9	1.8	30-40
TC6Q2558	03469	4 - 6 5/8	102 - 168	15	381	3.9	1.8	R2558
TC8Q	04158	6 ¼ - 10	159 - 254	26	660	8.0	3.6	30-40

*Spare "O" Cutter Wheel in Knob. CUTTER WHEELS ON P. 7 - 9

QUICK RELEASE™ CUTTERS FOR PLASTIC ON P. 25

TUBING CUTTERS

FEATURES

- Large, ergonomic grip knob for hand comfort during use.
- Internal reamer in T10 and T15 grip knob for operator convenience.
- For lighter weight, T20 features aluminum construction.

Tubing cutters are a simple, durable design. Each has a screw feed with a large grip knob to make it easier to tighten the cutter. **T10** and **T15** are zinc alloy construction with a built-in reamer for convenient cutting then deburring. **T20** is larger but light due to its aluminum construction. It features a fold-out reamer. Wide rollers on all three models yield a square cut while thin cutter wheel profile ensures a quick, clean cut.

Catalog No.	Item Code	O.D. Capacity		Weight		Cutter Wheel**			
		actual O.D. in	actual O.D. mm	lbs	kg	Copper	PE	PVC	
T10	03483	¹/a - 1	3 - 25	0.9	0.4	0	OP2	1 - 2PVC	
T15	03485	3/16 - 1 1/4	4 - 32	1.3	0.6	0	OP2	1 - 2PVC	
T20*	0.3487	5/8 - 2 1/8	15 - 54	1.5	0.7	n	OP2	1 - 2PVC	

^{**}Ships with wheel for copper. To cut PE or PVC pipe, order recommended cutter wheel separately.
*AWWA Approved for Tapping Contest.

CUTTER WHEELS ON P. 7 - 9



