



Tape Conductor – TCECT5060



- Lower impedance than equivalent sized round conductor
- Used for lightning protection system downconductor or grounding applications



Part Number	TCECT5060
Material	Copper
Finish	Tinned
Width (W)	50 mm
Thickness (T)	6 mm
Length (L)	20 m
Unit Weight	2.68 kg
Complies With	IEC® EN 62561-2
Certifications	Qualifoudre
Standard Packaging Quantity	20 m
UPC	78285690606
EAN-13	8711893105650

Cut-to-order (CTO) lengths are available for an additional charge.
Unit weight is per meter [3.28'].

IEC is a registered trademark of the International Electrotechnical Commission.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.