


Copper-Bonded Ground Rod, Pointed



- 99.9% pure electrolytic copper coating
- Molecular bond to nickel-sealed high strength steel core
- Rods have a high carbon steel core and tip that provide superior strength when driving
- Copper coating will not crack when bent or tear when driven
- Minimum copper coating of 10 mils on rods listed to UL® 467
- nVent ERICO name, length, diameter and part number is roll-stamped within 12" (304,8 mm) of chamfered end
- UL logo and control number where applicable stamped on each rod for easy inspection after installation



Material: Copper-Bonded Steel
Tensile Strength: 552 MPa Min



Part Number	Ground Rod Diameter, Nominal	Ground Rod Diameter, Actual Ø	Length L	Plating Thickness	Unit Weight	UPC Label	Complies With	Certifications
613840	3/8"	9.0 mm	1.2 m	254 µm	0.570 kg	No	-	-
613850	3/8"	9.0 mm	1.5 m	254 µm	0.730 kg	No	-	-
613860	3/8"	9.0 mm	1.8 m	254 µm	0.900 kg	No	-	-
613880	3/8"	9.0 mm	2.4 m	254 µm	1.230 kg	No	-	-
611330	1/2"	12.7 mm	0.9 m	254 µm	0.980 kg	No	-	-
6113330	1/2"	12.7 mm	1.0 m	254 µm	1.003 kg	No	IEC® EN 62561-2	-
611340	1/2"	12.7 mm	1.2 m	254 µm	1.260 kg	No	-	-
611350	1/2"	12.7 mm	1.5 m	254 µm	1.570 kg	No	-	-
611353	1/2"	12.7 mm	1.5 m	330 µm	1.670 kg	No	-	-
611360	1/2"	12.7 mm	1.8 m	254 µm	2.010 kg	No	-	-
611370	1/2"	12.7 mm	2.1 m	254 µm	2.108 kg	No	IEC® EN 62561-2	-
611380	1/2"	12.7 mm	2.4 m	254 µm	2.510 kg	No	ANSI®/ NEMA® GR1	UL
611300	1/2"	12.7 mm	3.0 m	254 µm	3.110 kg	No	ANSI®/ NEMA® GR1	CSA, cULus

Part Number	Ground Rod Diameter, Nominal	Ground Rod Diameter, Actual Ø	Length L	Plating Thickness	Unit Weight	UPC Label	Complies With	Certifications
611303	1/2"	12.7 mm	3.0 m	330 µm	3.350 kg	No	ANSI®/ NEMA® GR1	cULus
615830	5/8"	14.2 mm	0.9 m	254 µm	1.130 kg	No	IEC® EN 62561-2	-
6158330	5/8"	14.2 mm	1.0 m	254 µm	1.237 kg	No	IEC® EN 62561-2	-
615840	5/8"	14.2 mm	1.2 m	254 µm	1.540 kg	No	IEC® EN 62561-2	-
615843	5/8"	14.2 mm	1.2 m	330 µm	1.540 kg	No	IEC® EN 62561-2	-
615850	5/8"	14.2 mm	1.5 m	254 µm	1.920 kg	No	IEC® EN 62561-2	-
615853	5/8"	14.2 mm	1.5 m	330 µm	2.040 kg	No	IEC® EN 62561-2	-
615860	5/8"	14.2 mm	1.8 m	254 µm	2.300 kg	No	IEC® EN 62561-2	-
615863	5/8"	14.2 mm	1.8 m	330 µm	2.450 kg	No	IEC® EN 62561-2	-
6158660	5/8"	14.2 mm	2.0 m	254 µm	2.477 kg	No	IEC® EN 62561-2	-
615870	5/8"	14.2 mm	2.1 m	254 µm	2.600 kg	No	-	-
615880	5/8"	14.2 mm	2.4 m	254 µm	3.070 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	UL
615883	5/8"	14.2 mm	2.4 m	330 µm	3.080 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	UL
615800	5/8"	14.2 mm	3.0 m	254 µm	3.850 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	CSA, cULus
615803	5/8"	14.2 mm	3.0 m	330 µm	3.830 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
615812	5/8"	14.2 mm	3.7 m	254 µm	4.540 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
615815	5/8"	14.2 mm	4.6 m	254 µm	5.780 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
615950	5/8"	16.0 mm	1.5 m	254 µm	2.350 kg	No	-	-
615980	5/8"	16.0 mm	2.4 m	254 µm	3.870 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	UL
615900	5/8"	16.0 mm	3.0 m	254 µm	4.760 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
613440	3/4"	17.3 mm	1.2 m	254 µm	2.550 kg	No	IEC® EN 62561-2	-
613450	3/4"	17.3 mm	1.5 m	254 µm	2.810 kg	No	IEC® EN 62561-2	-
613460	3/4"	17.3 mm	1.8 m	254 µm	3.400 kg	No	IEC® EN 62561-2	-
613470	3/4"	17.3 mm	2.1 m	254 µm	3.835 kg	No	IEC® EN 62561-2	-
613480	3/4"	17.3 mm	2.4 m	254 µm	4.560 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	UL
613483	3/4"	17.3 mm	2.4 m	330 µm	4.540 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	UL

Part Number	Ground Rod Diameter, Nominal	Ground Rod Diameter, Actual \emptyset	Length L	Plating Thickness	Unit Weight	UPC Label	Complies With	Certifications
613400	3/4"	17.3 mm	3.0 m	254 μ m	5.720 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	CSA, cULus
613403	3/4"	17.3 mm	3.0 m	330 μ m	5.630 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
613412	3/4"	17.3 mm	3.7 m	254 μ m	6.770 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
613415	3/4"	17.3 mm	4.6 m	254 μ m	8.390 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
693400	3/4"	19.1 mm	3.0 m	254 μ m	5.600 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	cULus
693450	3/4"	19.1 mm	1.5 m	254 μ m	2.800 kg	No	-	-
693480	3/4"	19.1 mm	2.4 m	254 μ m	4.560 kg	No	IEC® EN 62561-2, ANSI®/ NEMA® GR1	UL
614400	1"	23.2 mm	3.0 m	254 μ m	10.000 kg	No	ANSI®/ NEMA® GR1	CSA, cULus

For rods to be listed to UL® 467, they must be at least 8' (2.43 m) in length.

IEC® EN 62561-2 supercedes EN 50164-2.

Additional lengths available.

ANSI is a registered trademark of American National Standards Institute. CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association. IEC is a registered trademark of the International Electrotechnical Commission. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.