

# NAVARA S1P SRC

PIGMENTED SPLIT LEATHER SHOES - S1P HRO CI HI SRC

Ref. NAVARAS1P

## Product specifications

Upper: Buffalo pigmented split leather. Lining: Polyamide absorbing. Insole: Removable preformed-Polyester on EVA. Midsole: Injected - Panorubber®. Outsole: Rubber Nitrile.

### COLOUR

Black

### SIZE

36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48

## Product Use - Risks

Antistatic Cutting / Perforation	Heat	Shock Slip		
Construction / Civil engineering Oil / Gas	Mining		Heavy industry	Light industry

## Product's highlights & user's benefits

### PANORUBBER® OUTSOLE

#### 1- SLIP RESISTANCE

Rubber outsole SRC standard  
Slip resistance on all type of slippery floor

#### 2- OIL RESISTANCE

Rubber/Nitrile outsole

#### 3- RESISTANCE TO HYDROLYSIS

The material remains stable and keeps its shapes during variations in temperature and humidity

#### 4- HEAT RESISTANCE

- HRO standard :  
300° Contact-heat resistant sole assembly (1 mins)

- HI standard :  
Isolation of the foot in the shoe against the heat. Raising the temperature does not exceed 22°C after 30 mins in a sand bath at 150°C

---

METAL

## Certifications and Standards

### PPE DIRECTIVE 89/686/EEC


EN ISO 20344:2011 Personal protective equipment - Test methods for footwear

EN ISO 20345:2011 Personal protective equipment - Safety footwear.

S1P HRO HI CI: Additional special requirements

SRC: Slip resistance

## References

References	Bar code	COLOUR	SIZE		
NAVARSPNO36	3295249150877	Black	36	5	-
NAVARSPNO37	3295249150884	Black	37	5	-
NAVARSPNO38	3295249150891	Black	38	5	-
NAVARSPNO39	3295249150907	Black	39	5	-
NAVARSPNO40	3295249150914	Black	40	5	-
NAVARSPNO41	3295249150921	Black	41	5	-
NAVARSPNO42	3295249150938	Black	42	5	-
NAVARSPNO43	3295249150945	Black	43	5	-
NAVARSPNO44	3295249150952	Black	44	5	-
NAVARSPNO45	3295249150969	Black	45	5	-
NAVARSPNO46	3295249150976	Black	46	5	-
NAVARSPNO47	3295249150983	Black	47	5	-
NAVARSPNO48	3295249150990	Black	48	5	-