

HAR44EL

FALL ARRESTER HARNESS WITH BELT - 4 ANCHORAGE POINTS - DIELECTRIC

Ref. HAR44EL_

Product specifications

Dielectric harness with positioning belt. 2 fall arrester anchorage points (back - front). 4 adjustable buckles. Positioning belt with thermoformed back closed with wide Velcro for more comfort. 180° rotation. 2 lateral anchorage points for work positioning. Sponge back lining. Buckles with plastic coating. Material insulates to 20kV.

Straps: Polyester.

Buckles: 100% plastic coating.

COLOUR

Black-Grey

SIZE

S/M/L, XL/XXL

Product Use - Risks

Fall

Construction / Civil engineering

Oil / Gas

Wind energy

Heavy industry

Services / Logistics

Vertical movement on a permanent structure
inclined surface

Short vertical movement or movement on inclined surface (less than 3 m)

Vertical movement, confined space

Long movement with multi connection /disconnection

Work positioning

Restraint

Long horizontal movement on horizontal surface

Long horizontal movement on vertical structure

Short horizontal movement (less than 3 m)

Product's highlights & user's benefits

DIELECTRIC

2 accessory attachment holders incorporated into the belt

Rotation 180°

Certifications and Standards

PPE DIRECTIVE 89/686/EEC

EN363 : 2008 Personal fall protection equipment - Personal fall protection systems

EN364 : 1992 Personal fall protection equipment : Test method

EN365 : 2004 General requirements for the instructions for use and the marking

EN361 : 2002 Personal protection equipment against falls from a height - Full body harnesses

EN358 : 1999 Personal fall protection equipment for work positioning and prevention of falls from a height - Belts for work positioning and restraint and work positioning lanyards.

References

References	Bar code	COLOUR	SIZE		
HAR44ELGT	3295249203504	Black-Grey	S/M/L	5	-
HAR44ELXX	3295249204723	Black-Grey	XL/XXL	5	-