




HEX REDUCER FEMALE/MALE XP-RZW



Ultra Cover XP


Usage: change of the metric thread diameter; connection of two various metric threads, external and internal.

Permissible load



Thread M ₁ /M ₂	Weight [kg]	Quantity [pcs/pkg]	Designation for the order	Catalogue number
M8/M10	0,010	20/50	XP-RZW-M8/10	81401108108
M10/M12	0,020	25	XP-RZW-M10/12	81401110128
M10/M16	0,060	5	XP-RZW-M10/16	81401110168
M12/M8	0,018	5	XP-RZW-M12/8	81401112088
M12/M16	0,060	5	XP-RZW-M12/16	81401112168

HEX HEAD BOLT XP-105



Ultra Cover XP

Usage: it is an element of screw connection; for the realization of all connections; the thread is present on the whole length.

Bolts of 5.8 class

Permissible load



Thread M	Length L [mm]	Quantity [pcs/pkg]	Quantity [pcs/kg]	Designation for the order	Catalogue number
M8	30	50	67	XP-105-M8X30	81402080308
M8	80	50	32	XP-105-M8X80	81402080808
M10	30	50	34	XP-105-M10X30	81402100308
M10	60	25	24	XP-105-M10X60	81402100608
M10	80	20	19	XP-105-M10X80	81402100808
M12	30	25	25	XP-105-M12X30	81402120308
M12	80	20	13	XP-105-M12X80	81402120808
M12	120	25	9	XP-105-M12X120	81402121208

PRODUCTS IN ULTRA
COVER XP COATING

HEX HEAD BOLT XP-105 ■ HEX REDUCER FEMALE/MALE XP-RZW