



ITX 19 L

SCREWDRIVER BIT SOCKETS

1/2"

for recessed TORX® head screws, long pattern

- > Manually operated sockets with knurled base.
- > 1/2" square drive.
- > Chrome Vanadium steel 31CrV3.
- > Bits: Molybdenum tool steel.



TORX® = Registered trademark of Acument Intellectual Properties, LLC. USA.

| Code | Ø mm | ⊕ | ▨ M | ★ mm | ↳ mm ▷ | ↕ kg |
|--------|------------|-----|---------|-------|--------|-------|
| 024210 | ITX19L T20 | T20 | M4-M5 | 3.86 | 100 | 0.095 |
| 024215 | ITX19L T25 | T25 | M4.5-M5 | 4.43 | 100 | 0.095 |
| 024220 | ITX19L T27 | T27 | M4.5-M6 | 4.99 | 100 | 0.096 |
| 024225 | ITX19L T30 | T30 | M6-M7 | 5.52 | 100 | 0.096 |
| 024230 | ITX19L T40 | T40 | M7-M8 | 6.65 | 100 | 0.096 |
| 024235 | ITX19L T45 | T45 | M8-M10 | 7.82 | 100 | 0.098 |
| 024240 | ITX19L T50 | T50 | M10 | 8.83 | 100 | 0.124 |
| 024245 | ITX19L T55 | T55 | M12 | 11.22 | 100 | 0.151 |
| 024250 | ITX19L T60 | T60 | M14 | 13.25 | 100 | 0.197 |
| 024253 | ITX19L T70 | T70 | M16 | 15.55 | 100 | 0.277 |

IKS 19

SCREWDRIVER BIT SOCKETS

1/2"

for cross-head screws PH

- > Manually operated sockets with knurled base.
- > 1/2" square drive.
- > Sockets: Chrome Vanadium steel 31CrV3.
- > Bits: Molybdenum tool steel.
- > Socket with Phillips & POZZIDRIV® Bits



| Code | Ø mm | ↳ mm ▷ | ↕ kg |
|--------|-------------|--------|-------|
| 665665 | IKS19 NO. 2 | 60 | 0.075 |
| 665673 | IKS19 NO. 3 | 60 | 0.080 |
| 665711 | IKS19 PZD 2 | 60 | 0.070 |
| 665738 | IKS19 PZD 3 | 60 | 0.080 |

ITX 19 B

SCREWDRIVER BIT SOCKETS 1/2"

for recessed TORX® head screws with pilot

- > Manually operated sockets with knurled base.
- > Chrome Vanadium steel 31CrV3.
- > Bits: Molybdenum tool steel.
- > 1/2" square drive.
- > Tamper proof.



TORX® = Registered trademark of Acument Intellectual Properties, LLC. USA.

*WHILE STOCKS LAST

| Code | Ø mm | ⊕ | ▨ M | ★ mm | ↳ mm ▷ | ↕ kg |
|---------|-------------|-----|---------|------|--------|-------|
| 6192720 | ITX19B T20* | T20 | M4-M5 | 3.86 | 55 | 0.075 |
| 6195660 | ITX19B T25* | T25 | M4.5-M5 | 4.43 | 55 | 0.075 |
| 6196390 | ITX19B T27* | T27 | M4.5-M6 | 4.99 | 55 | 0.076 |
| 6200170 | ITX19B T30 | T30 | M6-M7 | 5.52 | 55 | 0.076 |
| 6200410 | ITX19B T40 | T40 | M7-M8 | 6.65 | 55 | 0.091 |

TX 19

SOCKETS 1/2"

for protruding TORX® head screws

- > Manually operated sockets with thin walls and knurled base.
- > Chrome Vanadium steel 31CrV3.
- > 1/2" square drive.
- > Chrome plated.



TORX® = Registered trademark of Acument Intellectual Properties, LLC. USA.

| Code | NO. | ⊕ | ▨ M | ★ mm | ↳ mm ▷ | ↕ kg |
|--------|-----------|-----|---------|-------|--------|-------|
| 665908 | TX19 E 10 | E10 | M8 | 9.42 | 38.0 | 0.055 |
| 665916 | TX19 E 11 | E11 | - | 10.08 | 38.0 | 0.055 |
| 665924 | TX19 E 12 | E12 | M10 | 11.17 | 38.0 | 0.055 |
| 665932 | TX19 E 14 | E14 | M12 | 12.90 | 38.0 | 0.055 |
| 665940 | TX19 E 16 | E16 | M12 | 14.76 | 38.0 | 0.060 |
| 665959 | TX19 E 18 | E18 | M14 | 16.70 | 40.0 | 0.080 |
| 665967 | TX19 E 20 | E20 | M6 | 18.45 | 40.0 | 0.085 |
| 665975 | TX19 E 24 | E24 | M18-M20 | 22.16 | 41.5 | 0.115 |