Ratchets (1/4")

_ i

2093 U-3 REVERSIBLE RATCHET 1/4"

- > Especially for working in confined spaces, as in the automotive business.
- > According to DIN 3122, ISO 3315.
- > With non-slip metal disc change, fine-toothed (72 teeth) and robust.
- > Return angle of five degrees.
- > Non-slip 2-component handle with hanging hole.
- > For hand-operated sockets and accessories with square drive as per DIN 3120 C 6.3, ISO 1174.
- > Ball locking device.
- > Gedore vanadium steel 31CrV3, chrome plated.



Code	No.	•,		£°	∢ mm ►	$\Delta_{kg}^{\dagger}\Delta$
6170590	2093 U-3	1/4	6.3	5	129	0.095

2093 U-10



REVERSIBLE RATCHET 1/4"

- > Particularly for the demanding use experienced in industry and with utility vehicles.
- > According to DIN 3122, ISO 3315.
- > With recessed lever change, locks in middle position.
- > Return angle of five degrees.
- > Non-slip 2-component handle with hanging hole.
- > For hand-operated sockets and accessories with square drive as per DIN 3120 C 6.3, ISO 1174.
- > Ball locking device.
- > Gedore vanadium steel 31CrV3, chrome plated.



Code	No.			4°	∢ mm ⊳	$\Delta_{kg}^{\dagger}\Delta$
6180470	2093 II_10	1/4	63	15	129	n 1ng

2093 Z-94

RATCHET HANDLE WITH COUPLER 1/4"

- > Used throughout industry and the automotive world.
- **>** According to DIN 3122, ISO 3315.
- > With square coupler, medium-fine toothed, extremely rugged.
- > Return angle of eighteen degrees.
- > For hand-operated sockets and accessories with square drive as per DIN 3120 C 6.3, ISO 1174.
- > Ball locking device.
- > Gedore vanadium steel 31CrV3, chrome plated.

Sockets (1/4")

20 (MM)SOCKETS 1/4"

hexagon

- > Manually operated sockets with knurled base.
- > Chrome Vanadium steel 31CrV3.
- > Chrome plated and polished.
- > In accordance with SANS 1113 and DIN 3120.



Code	No.	•,		4.0	∢mm ►	Δ_{kg}
6170750	2093 Z-94	1/4	6.3	18	129	0.076





Code	<u> </u>	∢mm ►	$\Delta_{kg}^{+}\Delta$
6165400	No.20 4mm	25	0.009
6165670	No.20 5mm	25	0.010
6165830	No.20 6mm	25	0.010
6165910	No.20 7mm	25	0.012
6166050	No.20 8mm	25	0.014
6166130	No.20 9mm	25	0.016
6166210	No.20 10mm	25	0.020
6166480	No.20 11mm	25	0.025
6166560	No.20 12mm	25	0.030
6166640	No.20 13mm	25	0.035

[1/4"]