

8455/2-4,7k Ω -0/10-6 Art. No. 218543



- Easy adjustment of desired value on the potentiometer
- Resistance range of 100 Ω to 1 M Ω , 2 W power
- Optional delivery with connection line or terminals

WebCode **8455A**



R. STAHL Series 8455 potentiometers are intended for installation in panels and are delivered with a connection line or with terminals. Their resistance is between 100 Ω and 1 M Ω , they are designed for 2 W power. The desired value can be adjusted easily and conveniently via the rotary actuator.

Technical Data

Explosion Protection

Application range (zones)	1 2 21 22
IECEEx gas certificate	IECEEx PTB 07.0002 X
IECEEx gas explosion protection	Ex db mb IIC T6 ... T5
IECEEx dust certificate	IECEEx PTB 07.0002 X
IECEEx dust explosion protection	Ex tb T80 °C / T95 °C
ATEX gas certificate	PTB 02 ATEX 2156 X
ATEX gas explosion protection	Ex II 2 G Ex db mb IIC T6 ... T5
ATEX dust certificate	PTB 02 ATEX 2156 X
ATEX dust explosion protection	Ex II 2 D Ex tb T80 °C / T95 °C
Certificates	ATEX (PTB), IECEEx (PTB)

Electrical Data

Rated operational voltage AC	400 V
Rated operational power	2 W
Nominal value	4,7 k Ω
Maximum resistance $R_{\max}$	4700 Ω
Minimum resistance $R_{\min}$	100 Ω
Characteristic	Linear
Accuracy	20 %
Resistor material	Carbon composition

Ambient Conditions

Ambient temperature	-20 °C ... +40 °C (T6) -20 °C ... +55 °C (T5)
---------------------	--


Mechanical Data

Degree of protection (IP)	IP66
Enclosure material	Polyamide




8455/2-4,7kΩ-0/10-6 Art. No. 218543

Mechanical Data	
Silicone-free	Yes
Conductor length	6 m
Type of connection cable	HO5VV-F, 3 x 0.75
Depth of cut-out	130 mm
Rotary actuator labelling	0 ... 10
Adjustment range	270°
Torque	0,7 ... 2 Ncm
Impact resistance	100 Ncm
Weight	0.6 kg
Weight	1.32 lb
Mounting / Installation	
Connection type	Connection line

Technical Drawings – Subject to Alterations



Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Drilling pattern: for aligning several devices Ø 38 mm, in a panel

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.