

BI-METAL

INTENSS™ PRO

- Complete line with a full range of widths and pitches to suit a variety of cutting needs
- Unique tooth geometry provides intense production cutting in ferrous and non-ferrous metals



INTENSSPRO

| Catalog Number | Unit Price (US\$) | | Alternative for # MTO | | Width x Thickness mm | Width x Thickness inch | DPP |
|-------------------|-------------------|--------------|-----------------------|---------------------|----------------------|------------------------|--------|
| | Meter | Feet | Roll Production | MTS (Make to Stock) | | | |
| # IP19X3-4/P | 10,67 | 3,25 | IT19X3-4/P | | 19,0 x 0,90 | 3/4" x .035" | 3-4 |
| # IP19X4-6/P | | | IT19X4-6/S | | | | 4-6 |
| # IP19X5-8/P | | | IT19X5-8/S | | | | 5-8 |
| # IP19X6-10/P | | | IT19X6-10/S | | | | 6-10 |
| IP27X2-3/P | 11,58 | 3,53 | - | | 27,0 X 0,90 | 1" X .035" | 2-3 |
| IP27X3-4/P | | | - | | | | 3-4 |
| IP27X4-6/P | | | - | | | | 4-6 |
| IP27X5-8/P | | | - | | | | 5-8 |
| # IP27X6-10/P | | | IT27X6-10/S | | | | 6-10 |
| IP27X3/B | | | - | | | | 3 |
| # IP34X1.4-2/P | 16,45 | 5,02 | - | | 34,0 X 1,10 | 1.1/4" X .042" | 1.4-2 |
| IP34X2-3/P | | | - | | | | 2-3 |
| IP34X3-4/P | | | - | | | | 3-4 |
| IP34X4-6/P | | | - | | | | 4-6 |
| IP34X5-8/P | | | - | | | | 5-8 |
| # IP34X6-10/P | | | IT34X6-10/S | | | | 6-10 |
| IP41X1-1.2/P | 19,83 | 6,05 | - | | 41,0 X 1,30 | 1.1/2" X .050" | 1-1.2 |
| IP41X1.4-2/P | | | - | | | | 1.4-2 |
| IP41X2-3/P | | | - | | | | 2-3 |
| IP41X3-4/P | | | - | | | | 3-4 |
| IP41X4-6/P | | | - | | | | 4-6 |
| IP41X5-8/P | | | - | | | | 5-8 |
| IP54X.8-1.3/P | 33,53 | 10,21 | - | | 54,0 x 1,60 | 2" x .063" | .8-1.3 |
| IP54X1-1.2/P | | | - | | | | 1-1.2 |
| IP54X1.4-2/P | | | - | | | | 1.4-2 |
| IP54X2-3/P | | | - | | | | 2-3 |
| IP54X3-4/P | | | - | | | | 3-4 |
| IP54X4-6/P | | | - | | | | 4-6 |
| IP67X1-1.2/P | 38,96 | 11,86 | - | | 80,0 x 1,60 | 3.1/8" x .063" | 1-1.2 |
| IP67X1.4-2/P | | | - | | | | 1.4-2 |
| IP80X.8-1.3/P | 68,06 | 20,75 | - | | 80,0 x 1,60 | 3.1/8" x .063" | .8-1.3 |
| IP80X1-1.2/P | | | - | | | | 1-1.2 |
| # IP80X1.4-2/P | | | - | | | | 1.4-2 |
| Tooth Type | | | | | | | |
| Positive P | | | | | | | |

On request MTO (Make To Order)
 MOQ (Minimum Order Quantity) = IP19 and IP27: 3.000 m or 10.000 ft - IP34: 1.500 m or 4.920 ft - IP54 and IP67: 400 m or 1.310 ft
 Shipping time (ex-stock) = 30 days.

BI-METAL

INTENSTM PRO

- Faster and straighter cuts
- Improved fatigue and wear resistance
- Ideal for production cutting across a wide range of metals
- For solids and thick wall tubes



| Price per Welding - US\$ | |
|--------------------------|--------------|
| IP 19 to 27mm | 4,42 |
| IP 34 to 41mm | 8,19 |
| IP 54 to 80 mm | 15,91 |

Available in welded bands for all widths and in production coils for widths from 19 to 41mm Coils with approximately 90m Welded Band: multiply by the measure of the band and add the welding cost. E.g. IP34x3-4/P-3,50.
 For widths from 27 to 41 mm with lengths up to 6 meters, supplied in Boxes with 5 Units, above 6 meters in Boxes with 1 Unit for all widths.

