

## Pipe Cutter

# 220

for steel pipes

- › Heavy duty pipe cutters.
- › Frame in malleable cast steel.
- › TUBEX®



| Code    | No.           | Ø mm  | Wall thickness | l mm | kg   |
|---------|---------------|-------|----------------|------|------|
| 4503400 | 220020 1/8-2" | 10-60 | 2.0-6.3        | 380  | 2.90 |

| Code   | No.         |
|--------|-------------|
| 220220 | Spare Wheel |

## Tin Snips

# 8516

scissors pattern

- › American Pattern.
- › Carbon steel SAE1045.
- › Drop forged and heat treated.
- › Cutting surfaces induction hardened.
- › Precision ground cutters.
- › Blue epoxy powder coated.



| Code   | No.      | l mm | kg    |
|--------|----------|------|-------|
| 675504 | 8516/250 | 250  | 0.525 |
| 675547 | 8516/300 | 300  | 0.675 |

# 8531

straight pattern

- › English Pattern.
- › Carbon steel SAE1045.
- › Drop forged and heat treated.
- › Cutting surfaces induction hardened.
- › Precision ground cutters.
- › Blue epoxy powder coated.



| Code   | No.                        | l mm | kg    |
|--------|----------------------------|------|-------|
| 675784 | 8531/200 Left-hand Cutting | 200  | 0.290 |
| 675792 | 8531/250 Left-hand Cutting | 250  | 0.455 |
| 675806 | 8531/300 Left-hand Cutting | 300  | 0.660 |

# 424

ideal pattern snips

- › For straight continuous and figure cuts.
- › With lever action.
- › Self-opening with installed spring and lock.
- › Polished cutting edges.
- › Sheet thickness maximum 1.2mm at strength of 600N/mm².
- › Non-slip two-component handles.



| Code    | No.                        | l mm | kg  |
|---------|----------------------------|------|-----|
| 4515410 | 424-260 Right-hand Cutting | 160  | 530 |

# 425

figure snips

- › For straight continuous and figure cuts.
- › With lever action.
- › Self-opening with installed spring and lock.
- › Polished cutting edges.
- › Sheet thickness maximum 1.2mm at strength of 600N/mm².
- › Non-slip two-component handles.



| Code    | No.                        | l mm | kg  |
|---------|----------------------------|------|-----|
| 4515760 | 425-260 Right-hand Cutting | 260  | 480 |