

## VDE 2 E

### VDE SINGLE ENDED RING SPANNERS

deep offset

- Gedore Vanadium steel 31CrV3.
- VDE insulation up to 1000 V, according to EN 60900/IEC 60900, two-ply Check-Tool insulation.



VDE 2 E 19



VDE 2 E 13

| Code    | No.         | l mm | mm | kg    |
|---------|-------------|------|----|-------|
| 6036000 | VDE 2 E10mm | 170  | 10 | 0.097 |
| 6036190 | VDE 2 E11mm | 180  | 11 | 0.093 |
| 6036350 | VDE 2 E13mm | 190  | 13 | 0.130 |
| 6036430 | VDE 2 E14mm | 210  | 14 | 0.151 |
| 6036780 | VDE 2 E17mm | 220  | 17 | 0.199 |
| 6036860 | VDE 2 E19mm | 240  | 19 | 0.244 |
| 6037320 | VDE 2 E32mm | 330  | 32 | 0.683 |

## VDE 894

### VDE SINGLE OPEN ENDED SPANNERS

- Gedore Vanadium steel 31CrV3.
- VDE insulation up to 1000 V, according to EN 60900/IEC 60900, two-ply Check-Tool insulation.
- Jaw set at 15°.



VDE 894 12



VDE 894 22

| Code    | No.          | l mm | mm | kg    |
|---------|--------------|------|----|-------|
| 6572120 | VDE 894 10mm | 105  | 10 | 0.034 |
| 6572200 | VDE 894 11mm | 115  | 11 | 0.044 |
| 6572470 | VDE 894 13mm | 135  | 13 | 0.067 |
| 6572550 | VDE 894 14mm | 145  | 14 | 0.081 |
| 6572980 | VDE 894 17mm | 160  | 17 | 0.117 |
| 6573010 | VDE 894 19mm | 175  | 19 | 0.161 |
| 6574920 | VDE 894 32mm | 280  | 32 | 0.558 |

## VDE 2133

### NUT DRIVERS

with 3C handle

- 3-component handles Power-Grip<sup>3</sup> with hanging hole.
- Ergonomic handle design.
- Head depth 25mm, blade length 125mm.
- VDE insulation up to 1000 V, according to EN 60900/IEC 60900.



| Code    | No.         | l mm | mm | Head Ø | kg    |
|---------|-------------|------|----|--------|-------|
| 1747045 | VDE 2133 3  | 225  | 3  | 9      | 0.109 |
| 1747053 | VDE 2133 4  | 225  | 4  | 10     | 0.111 |
| 1747061 | VDE 2133 5  | 225  | 5  | 11     | 0.112 |
| 1747088 | VDE 2133 6  | 225  | 6  | 12     | 0.114 |
| 1747096 | VDE 2133 7  | 235  | 7  | 14     | 0.152 |
| 1747118 | VDE 2133 8  | 235  | 8  | 15     | 0.154 |
| 1747126 | VDE 2133 9  | 235  | 9  | 16     | 0.154 |
| 1747134 | VDE 2133 10 | 245  | 10 | 17     | 0.161 |
| 1747142 | VDE 2133 11 | 245  | 11 | 19     | 0.193 |
| 1747150 | VDE 2133 12 | 245  | 12 | 20     | 0.196 |
| 1747169 | VDE 2133 13 | 245  | 13 | 21     | 0.199 |
| 1747177 | VDE 2133 14 | 245  | 14 | 22     | 0.198 |
| 1747185 | VDE 2133 17 | 245  | 17 | 26     | 0.222 |

## VDE 2133

### NUT DRIVER SET

10 pieces



| Code    | No.           | Contents                                          | kg   |
|---------|---------------|---------------------------------------------------|------|
| 1747260 | VDE 2133 / 10 | 2133 5,0 6,0 7,0 8,0 9,0 10,0 11,0 12,0 13,0 14,0 | 1.30 |

- Only tools bearing these test symbols are classed as insulated tools.
- VDE insulation as per standard EN60900, IEC/CEI900, VDE0680.
- Safe working in high-voltage areas.
- Up to 1000V alternating current.
- Up to 1500V direct current.

