

V 62

ADJUSTABLE WRENCH

- › Chrome Vanadium steel 31CrV3.
- › Swedish pattern. Jaw set at 15°.
- › Blackened finish. Ground head.
- › Moulded PVC handle.
- › Insulated up to 1000V.
- › Protective guard.
- › Due to the adjusting knurl not being insulated,
- › this tool is not certified to VDE.



Code	No.	mm	mm	kg
636854	V 62 / 200H*	200	25	0.250
636858	V 62 / 250H	250	30	0.460
636862	V 62 / 300H	300	36	0.700

VDE 4507

TORQUE WRENCH 1/2"

5-50 N·m / 4-37 lbf·ft

- › Controlled screw tightening in the most common range of 5 - 50Nm / 4 - 37 lbf·ft.
- › Automatic short-path actuation with tactile impulse and audible signal.
- › Dual scale with a scale graduation of 5Nm and 5lbf·ft.
- › Fine toothed ratchet with square drive as per DIN 3120 - A 12.5, ISO 1174.
- › VDE insulation up to 1000V, according to EN 60900/IEC 60900, two-ply Check-Tool insulation.



Code	No.	mm	mm	mm	kg
6681920	VDE 4507-4	1/2	12.5	370	1.251

VDE 2160 PH

PHILLIPS SCREWDRIVERS

for cross-head screws PH

- › Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- › Blade tip to DIN ISO 8764-1 PH
- › 3-component handles Power-Grip³ with hanging hole
- › Ergonomic handle design enables precise and fatigue-free working
- › Positive-fit joint of handle and blade for optimum transmission of force
- › Type of drive marked at end of the handle
- › Blade from GEDORE molybdenum-vanadium-Plus tempered steel



Code	No.	mm	mm	mm	kg
1612115	VDE 2160 PH1	M2 - M3	1	180	0.082
1612123	VDE 2160 PH2	M3,5 - M5	2	210	0.119
1612131	VDE 2160 PH3	M5,5 - M7	3	270	0.188

VDE 2170

ELECTRICIAN'S SCREWDRIVERS

for slotted head screws

- › Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- › Tip to DIN ISO 2380-1 form B
- › 3-component handles Power-Grip³ with hanging hole
- › Ergonomic handle design enables precise and fatigue-free working
- › Positive-fit joint of handle and blade for optimum transmission of force
- › Type of drive marked at end of the handle
- › Blade from GEDORE molybdenum-vanadium-Plus tempered steel



Code	No.	mm	mm	mm	kg
1612220	VDE 2170 2,5	2.5		160	0.038
1612247	VDE 2170 3,5	3.5		185	0.055
1612255	VDE 2170 4	4.0		185	0.058
1612271	VDE 2170 5,5	5.5		225	0.095
1612298	VDE 2170 6,5	6.5		260	0.134

VDE 2160-2170

SCREWDRIVER SET

6 pieces



Code	No.	Contents	kg
1616048	VDE 2170-2160 PH 06	⊖ VDE 2170 3.5 4 5.5 6.5 ⊕ VDE 2160 PH1 PH2	660