8572

TORQUE WRENCH DREMOMETER

1500-3000Nm

Use:
- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

Features:
- Adjustable torque wrench with a 1.1/2" single square drive for controlled clockwise tightening.
- 1.1/2" square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Automatic short path actuation with tactile impulse and audible signal.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Full-metal construction from high strength aluminium alloy.
- Double scale with scale graduation of 50Nm.
- Extension tube with maximum lever length of 2343mm.
- Supplied with a calibration certificate.
- Unique serial number for traceability.

Code	Type	No.	■"	■	Contents		Nm	mm	kg
7717160		8572-01	1.1/2	40	with 2 extension tubes	50Nm	1500-3000	1423-2343	13.20

753

TORQUE WRENCH DREMOMETER MINI

2-12Nm

Use:
- For use in almost all industrial manufacturing areas.
- For controlled nut and bolt tightening.

Features:
- Adjustable torque wrench with a 1/4" single square drive for controlled clockwise tightening.
- 1/4" square drive with ball-locking mechanism as per DIN 3120.
- In accordance with DIN EN ISO 6789, traceable to national norms.
- Automatic short path actuation with tactile impulse and audible signal.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- Window with a magnifying-glass effect.
- Double scale with a scale graduation of 0.5Nm and 5 lbf·in.
- Additional micrometer scale for setting interim values with Nm, graduations of 0.05Nm
- Supplied with a calibration certificate.
- Unique serial number for traceability.

Code	Type	No.	■"	■	Contents		Nm	lbf·in	mm	kg
1957694	Mini	753-11	1/4	6.3	in plastic box	0,5Nm / lbf·in + 0,05Nm	2-12	18-106	211	0.320

8200

TORQUE ANGLE INDICATOR

Use:
- Additional angle regulated tightening for controlled torque and angle activation.

Features:
- For additional precise angle tightening (0 - 360°)
- 1/2" square drive with ball-locking device.
- With sliding magnetic and gripping arm.
- For use with a suitable torque wrench.
- The maximum output of the torque wrench must not be exceeded.

Code	No.	■"	□"	∅ mm	°	kg
1195980	8200-01	1/2	1/2	80	0-360	0.330