

DMK

TORQUE WRENCH DREMASTER®

20-850Nm / 15-630lbf·ft

- Use:**
- For use in all areas of industrial manufacturing.
 - For controlled nut and bolt tightening.
- Features:**
- Adjustable torque wrench with a square drive and integrated ratchet head function.
 - For controlled bi-directional tightening.
 - Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
 - In accordance with DIN EN ISO 6789, traceable to national norms.
 - Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
 - Sturdy, satin-chrome plated tubular steel construction, with chrome plated ratchet head and top grade plastic parts.
 - Ergonomically shaped, two-component plastic grip with calibration aid.
 - Double scale Nm and lbf.ft behind window with magnifying effect.
 - Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
 - Supplied with a calibration certificate.
 - Unique serial number for traceability.



Code	No.	□"	■	Nm	lbf·ft	سلسله	Scale ring	□ mm	⚖
2641232	DMK 100	1/2	12.5	20-100	15-75	5 N-m	0,5 N-m	423.5	1.10
2641240	DMK 200	1/2	12.5	40-200	30-150	10 N-m	1 N-m	514.5	1.30
2641259	DMK 300	1/2	12.5	60-300	45-220	10 N-m	1 N-m	606.4	1.50
2641267	DMK 400	3/4	20.0	80-400	60-300	10 N-m	1 N-m	714.8	2.40
2641275	DMK 550	3/4	20.0	110-550	80-405	10 N-m	1 N-m	953.2	3.80
2641283	DMK 750	3/4	20.0	150-750	110-550	10 N-m	1 N-m	1,228.2	4.90
2641291	DMK 850	3/4	20.0	250-850	185-630	10 N-m	1 N-m	1,375.2	5.20

DMSE

TORQUE WRENCH DREMASTER®

20-400Nm / 15-300lbf·ft

- Use:**
- For use in all areas of industrial manufacturing.
 - For controlled nut and bolt tightening.
- Features:**
- Adjustable torque wrench with a spigot end.
 - For controlled bi-directional tightening.
 - Interchangeable mushroom head square drive with ball-locking mechanism as per DIN 3120.
 - In accordance with DIN EN ISO 6789, traceable to national norms.
 - Lever breaking mechanism with a castor guarantee tactile impulse and audible actuation signals.
- Actuation accuracy: +/- 3% tolerance of the scale set to torque.
 - Sturdy, satin-chrome plated tubular steel construction, with chrome plated ratchet head and top grade plastic parts.
 - Ergonomically shaped, two-component plastic grip with calibration aid.
 - Double scale Nm and lbf.ft behind window with magnifying effect.
 - Additional micrometer scale with a Nm graduation of 0.1, 0.25, 0.5 or 1Nm.
 - Supplied with a calibration certificate.
 - Unique serial number for traceability.



Code	No.	□ mm	Nm	lbf·ft	سلسله	Scale ring	□ mm	⚖
2641445	DMSE 100	9x12	20-100	15-75	5 N-m	0,5 N-m	398.5	1.00
2641453	DMSE 150	9x12	30-150	22-110	10 N-m	1 N-m	489.5	1.16
2641461	DMSE 200	14x18	40-200	30-150	10 N-m	1 N-m	499.5	1.25
2641488	DMSE 300	14x18	60-300	45-220	10 N-m	1 N-m	590.4	1.40
2641496	DMSE 400	14x18	80-400	60-300	10 N-m	1 N-m	677.2	2.00

1/2 3/4



9x12

