

nVent HOFFMAN GL66 Mild Steel Hinge Cover



SOLUTIONS FOR AUTOMATION & CONTROL DEVICES: ONE DOOR



INDUSTRY STANDARDS

Solid hinged cover models.
Mounting brackets required to meet UL/CSA external mounting requirements.

UL 508A listed; Type 4, 12; File No. E61997
cUL Listed per CSA C22. 2 No. 94; Type 4, 12; File No. E61997

NEMA/EEMAC Type 4, 12, 13
CSA, File No. 42186: Type 4, 12
IEC/EN62262 IK9
IEC 60529, IP66
IEC 62208



APPLICATION

- Automotive
- Packaging
- Material handling
- Tool and machine

SCOPE OF DELIVERY

- Enclosure with hinged door
- Gland plate(s), supplied loose (for items with gland plate)
- Mounting plate, supplied loose (for items with mounting plate)
- Assembly kit
- Installation instruction

FEATURES

- Reversible right-to-left, side-hinged door with simple, easy-to-remove and -install hinge pins
- 210 degree opening door that is easily removed by pulling clip-style hinge pins
- Quarter-turn latch with 3 mm double-bit insert
- Furnished hardware kit includes solid washers for wall-mounting, key hole plugs

SPECIFICATIONS

- Mild steel construction with doors thickness 1,5 to 2,0 mm and body thickness 1,2 or 1,5 mm
- External formed body flange
- Seamless foam-in-place gasket
- Grounding studs system
- Conductive panel available integrated as an option or as an accessory
- Solution with gland plate
- Weatherproof paint available on request

FINISH

- RAL 7035 textured light-gray polyester powder paint

