



Roxtec RM Ex solid compensation module

Roxtec RM modules are 60 mm (2.362") deep. The Ex version of the solid module is approved for use in hazardous locations and potentially explosive atmospheres.

- To be used with corresponding Roxtec components to form a complete sealing solution



Solid compensation module Ex

RM Ex

Product	Number of cables/pipes	For cable/pipe Ø (mm)	External dimensions WxHxD (mm)	Weight (kg)	Art. No
RM 5/0x24 Ex	0	0 - 0	5 x 5 x 60	0.05	EXRM00305241000
RM 10/0x12 Ex	0	0 - 0	10 x 10 x 60	0.1	EXRM00310121000
RM 15/0 Ex	0	0 - 0	15 x 15 x 60	0.02	EXRM00300151000
RM 20/0 Ex	0	0 - 0	20 x 20 x 60	0.04	EXRM00300201000
RM 30/0 Ex	0	0 - 0	30 x 30 x 60	0.08	EXRM00300301000
RM 30H90/0 Ex	0	0 - 0	30 x 90 x 60	0.25	EXRM00130901000
RM 40/0 Ex	0	0 - 0	40 x 40 x 60	0.14	EXRM00300401000
RM 40H80/0 Ex	0	0 - 0	40 x 80 x 60	0.28	153268
RM 60/0 Ex	0	0 - 0	60 x 60 x 60	0.33	EXRM00300601000