




## Roxtec RS UG™ seal

The Roxtec RS UG™ is a two-part seal for installation around single cables or pipes entering via foundations. It works as a long-lasting barrier against flooding, gas, humidity and rodents. The transit can be installed also in wet conditions and environments with running water. It withstands extreme cable bending and has a +5mm tolerance towards the aperture as well as an indicator showing when a compressed seal is achieved. The seal can be installed into sleeves, conduits and core drilled holes.

 For single cable or pipe



RS 110 UG



IMG\_6572 RS 200 UG WOC fix.tif



RS 110 UG

### With core

Product	For cable/pipe Ø (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
RS 70 UG	9 - 33	70 - 75	0.6	167234
RS 75 UG	9 - 33	75 - 80	0.7	186247
RS 80 UG	9 - 33	80 - 85	0.7	186248
RS 90 UG	24 - 53	90 - 95	0.9	167263
RS 95 UG	24 - 53	95 - 100	1	186249
RS 100 24-53 UG	24 - 53	100 - 105	1	186250
RS 100 UG	39 - 63	100 - 105	1.1	167236
RS 105 UG	39 - 63	105 - 110	1.2	186251
RS 110 UG	39 - 63	110 - 115	1.2	186252
RS 125 UG	55 - 88	125 - 130	1.6	167638
RS 130 UG	55 - 88	130 - 135	1.7	186253
RS 135 55-88 UG	55 - 88	135 - 140	1.7	186254
RS 135 UG	65 - 98	135 - 140	1.9	167240
RS 140 UG	65 - 98	140 - 145	2	186255
RS 145 UG	65 - 98	145 - 150	2	186256

**Without core**

Product	For cable/pipe Ø (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
RS 100 UG WOC	39 - 63	100 - 105	1	167265
RS 105 UG WOC	39 - 63	105 - 110	1	186257
RS 110 UG WOC	39 - 63	110 - 115	1.1	186258
RS 125 UG WOC	55 - 88	125 - 130	1.4	167639
RS 130 UG WOC	55 - 88	130 - 135	1.4	186259
RS 135 55-88 UG WOC	55 - 88	135 - 140	1.5	186260
RS 135 UG WOC	65 - 98	135 - 140	1.6	167266
RS 140 UG WOC	65 - 98	140 - 145	1.7	186261
RS 145 UG WOC	65 - 98	145 - 150	1.8	186262
RS 150 UG WOC	80 - 113	150 - 155	1.8	167246
RS 155 UG WOC	80 - 113	155 - 160	1.9	186263
RS 160 UG WOC	80 - 113	160 - 165	2	186264
RS 185 UG WOC	114 - 148	185 - 190	2.3	167258
RS 190 UG WOC	114 - 148	190 - 195	2.4	186265
RS 195 UG WOC	114 - 148	195 - 200	2.6	186266
RS 200 UG WOC	130 - 163	200 - 205	2.5	178151
RS 205 UG WOC	130 - 163	205 - 210	2.7	186267
RS 210 UG WOC	130 - 163	210 - 215	2.8	186268
RS 225 UG WOC	146 - 179	225 - 230	3.4	178166
RS 230 UG WOC	146 - 179	230 - 235	3.5	186269
RS 235 UG WOC	146 - 179	235 - 240	3.7	186270
RS 250 UG WOC	171 - 204	250 - 255	3.8	178178
RS 255 UG WOC	171 - 204	255 - 260	4	186271
RS 260 UG WOC	171 - 204	260 - 265	4.1	186272