

BRIK-CEN CM-10

DESCRIPTION

Monocomponent, elastic sealant based on a mixture of acrylic resins in water dispersion.

PROPERTIES

- ✓ Application temperature between +5°C and +35°C
- ✓ Elastic
- ✓ High quality
- ✓ No cracking
- ✓ Low ordo
- ✓ Indoor/Outdoor
- ✓ Paintable/varnishable
- ✓ Fast drying

APPLICATIONS

- Sealing of joints, baseboards in wood floors (parquet, floating floor,...)
- Sealing in wood carpentry (built-in cupboards, windows, doors)



Packaging	Capacity	Box quantity	Best before
Cartridges	300 ml	12 units	5 years
Tube	150 ml	12 units	5 years

COLORS

Oak, sapelli, pine, beech, cherry, pine, wengue, light grey, dark grey and white.

**Please contact us regarding the availability of other colors and packaging.*

TECHNICAL INFORMATION

Properties	Method	Unit	Value
Consistency			Pasty
Modulus at 100%	ISO 37	N/mm ²	0,09
Elongation at break	ISO 37	%	1184
Tensile strength	ISO 37	N/mm ²	0,12
Density		g/ml	1,06

DIRECTIONS FOR USE

- Before application: Clean the surface from dust and dirt.
- Cut off the cartridge tip, screw on the canula and cut it at a 45° angle to the desired diameter.
- It can be overpainted/varnished within approximately one hour of application .
- Compatible with paints and varnishes since the adhesion is not affected and avoid orange peel with varnishes.

ADHESION

Excellent adhesion on most common porous construction materials.

CLEANING

Uncured product can be cleaned with water. Once cured, the product can be removed mechanically.

HEALTH AND SAFETY

Safety data sheet available upon request of the client.

RECOMMENDED ACCESSORIES

Applicator gun P-1441
 cartridge



Note

The information contained in this document, as well as our technical advice whether verbal or written, is the result of our experience with the product and should be considered as collaboration without compromise, since the use and / or final application of our adhesives is beyond our control, declining all liability for improper use. The customer is responsible to confirm and evaluate prior to use, by trial or test the product conforms to required employment. So our guarantee is limited to ensure the quality of our products, according to our quality standards.

Quiadsa reserves the right to change the properties of its products. Users must know and use the latest updated version of the technical data sheets, Quiadsa will send them upon request or they can be downloaded on the website: www.quiadsa.com